

DKT-7288

2D Bluetooth Barcode Scanner



SPECIFICATION

PERFORMANCE

ILLUMINATION		White LED
Focusing		Red Light LED
SYMBOLOGIES	1D	EAN/JAN-8,13; UPC-A; UPC-E; CODE-128; CODE-93; RSS-Standard,Limited,Expanded; CODE-39; Inter-Leaved 2/5; Standard 2/5; Matrix 2/5; Industrial 2/5; China-Post; MSI; MSI-PLESSEY; CODE-BAR; CODE-11...;
	2D	QR Code, Data Matrix, PDF417
RESOLUTION		≥ 5mil
Typical DEPTH OF		EAN-13: 55mm-220mm (13mil)
READING WIDE		200mm~500mm
SCAN RATE		200 times/second
PRINT CONTRAST RATIO		≥ 25%
INDECATOR		LED, Beeper
FIELD OF VIEW		Horizontal : 34° , Vertical : 26°

MECHANICAL / ELECTRICAL

INTERFACE		USB (HID or V-COM), Bluetooth
WORKING VOLTAGE		DC 3.3 V
CURRENT	Operating	180mA
	Standby	USB 33mA;
DEMENSIONS		42mm*30.05mm*45.3mm
WEIGHT		30g (without cable)

ENVIRONMENTAL

OPERATING TEMPERATURE		-20℃ - +50℃
STORAGE TEMPERTURE		-40℃ - +70℃
HUMIDITY		5% - 95% (no-condensing)
Illumination Aiming		0 ~ 100,000 lux (nature light)
ESD		±9 KV (contact discharge); ±15 KV (air discharge)

SAFETY

EN55022: 2006+A1:2007 EN55024:1998+A1:2001+A2:2003