

NT-R2

Bluetooth 2D barcode scanner



Features

1. Bluetooth HID&SPP
2. Fast and accurate in reading 2D codes
3. Service life of button reaches up to 8 million times.
4. Resolution up to 2500
5. Very convenient to carry ring scanners

Feature

Light Resource	CMOS
Bluetooth Version	V 4.0 , HID mode , SPP mode
CPU	32 bit high resolution
Supported Symbolgies	2D: PDF417、QR Code (QR1/2, Micro)、Data Matrix (ECC200, ECC000, 050, 080, 100, 140)、Chinese Sensible Code 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11,
Charging time	2~3hour
Scans per charge	4000 times
Precision	≥ 3 mil (0.10mm)
Decode speed	5 in/s(12.7 cm)
Decode error rate	Less than 1/8 million
Depth of scan field	10-800mm
Print Contrast Signal	≥ 30°
scan angle	Yaw(Skew)45° & Pitch60°
Working Distance	Over 10meter
Battery capacity	360MAH

Mechanical / Electrical

Working Voltage	3.3 VDC ±5%
Current	working 230mA Standby: 3.4mA (RS232) , 54.0mA(USB)
Rated power consumption	186mW

Environment

Operating temperature	-20°C-45°C
Storage temperature	-20°C-45°C
Humidity	5%-85%

Optional:

Color :

Black



Interface :

USB cable



Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1

User's guide × 1

cable × 1



Packing details

scanner	Weight	50*30*45mm
	1pc/box; 120mm × 110mm × 50mm; 180g	270g;
Inner Box	100 sets/ctn;12kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	

Certifications

