

NT-R1

Bluetooth 1D Laser barcode scanner



Features

1. Factory direct sale, stable scanning
2. Fast and accurate in reading 1D codes
3. Service life of button reaches up to 8 million times.
4. Very convenient to carry ring scanners

Feature	
Light Resource	Laser
Bluetooth Version	V 4.0 , HID mode , SPP mode
CPU	32 bit high resolution
Supported Symbolgies	1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar, Code 93, Code 11,
Charging time	2~3hour
Scans per charge	6000 times
Precision	≥ 3 mil (0.10mm)
Decode speed	260 times/second
Decode error rate	Less than 1/8 million
Depth of scan field	10-800mm
Print Contrast Signal	≥ 30°
scan angle	Yaw(Skew)45° & Pitch60°
Working Distance	Over 30meter
Battery capacity	360MAH

Mechanical / Electrical

Working Voltage	3.3 VDC ±5%
Current	Receiving 26.6mA, Launching 24mA
Rated power consumption	80W

Environment

Operating temperature	-20°C-45°C
Storage temperature	-20°C-45°C
Humidity	5%-85%

Optional:

Color :

Black



Interface :

USB cable



Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

	Weight	50*30*45mm
scanner	1pc/box; 120mm × 110mm × 50mm; 180g	270g;
Inner Box	100 sets/ctn;12kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	

Certifications

