


NT-Z2S

Pocket Bluetooth 2D barcode scanner



Optional:



Features

1. Bluetooth HID&SPP
2. Service life of button reaches up to 8 million times.
3. Resolution up to 2500
4. Added screen display. Supports display of electricity and bar codes
5. Support for displaying Bluetooth connection status
6. Scanning barcode in addition to the buzzer ring also increased the vibration

Feature	
Light Resource	CMOS
Bluetooth Version	V 4.0 , HID mode , SPP mode
CPU	32 bit high resolution
Supported Symbolgies	2D: PDF417、QR Code (QR1/2, Micro)、Data Matrix (ECC200, ECC000, 050, 080, 100, 140)、Chinese Sensible Code 1D : Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4, Matrix 2 of 5, Industrial 25, Standard 25, Code39 , Codabar, Code 93, Code 11,
Charging time	2~3hour
Scans per charge	45000 times
Precision	≥ 4 mil (0.10mm)
Decode speed	5 in/s(12.7 cm)
Decode error rate	Less than 1/8 million
Depth of scan field	10-800mm
Print Contrast Signal	≥ 30°
scan angle	Yaw(Skew)45° & Pitch60°
Working Distance	0-10meter
Battery capacity	1000MAH

Mechanical / Electrical

Working Voltage	3.3 VDC ±5%
Current	working 230mA Standby: 3.4mA (RS232) , 54.0mA(USB)
Rated power consumption	186mW

Environment

Operating temperature	-20°C-45°C
Storage temperature	-20°C-45°C
Humidity	5%-85%

Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1	
User's guide × 1	
cable × 1	

Packing details

scanner	Weight	105*50*25mm
	1pc/box; 190mm × 115mm × 85mm; 220g	100g;
Inner Box	50 sets/ctn;12kg/ctn; 600mm×450mm×420mm	
Carton	10500pcs; 150ctns	
20FT Container	7500pcs; 150ctns	
	23800pcs; 325ctns	

Certifications

