

# Desktop Thermal Transfer Label Printer



## Print specification

Model	GP-1125T
Dot density	203 dots/inch(8dots/mm)
Print method	Thermal Transfer / Direct Thermal
Dot size(W×L)	0.125×0.125 mm (1 mm = 11.8 dots)
Print speed (inch/s)	2~5 inch/s
Maximum print width	104 mm(4.25")
Maximum print length	2286 mm(90")
Thermal film(reliability)	50KM

## Specifications

Dimention	210(W)×180(H)×285(L)
Weight	2.09KG
Power supply	Input: AC 100-240V Output: DC 24V 2.5A,60W
Environment	Work environment : temperature 5~40°C (41~104°F), humidity 25~85% Storage environment : temperature-40~60°C (-40~140°F), humidity 10~90%
Interface	Serial+USB+Parallel+Ethernet
Memory	RAM: 8M FLASH: 4M
Font Size	FONT 0 to FONT 8
Barcode type	1D: Code 39,Code 93,ITF,EAN 128, Code 128 subsets A,B,C,Codabar, JAN-8(EAN-8),JAN-13(EAN-13),UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI,MSIC,PLESSEY, CPOST,ITF 14,EAN 14, 2D: 2D Pharmacode, Aztec, Codeblock F, Datamatrix, Grid Matrix, GS 1 Datamatrix, Maxicode, MicroPDF, PDF-417, QR, Micro QR, GS 1 QR Code, DotCode, GS 1 DotCode
Enlargement&Rotation	1 to10 times enlargement in both directions; 0°, 90°, 270°, 360°rotation
Emulation	TSPL

## Ribbon specification

Ribbon diameter	Max. 67 mm
Ribbon length	300m
Ribbon axis size	1 inch (25.4 mm)
Ribbon width	Max. 110 mm Min. 30 mm
Ribbon winding method	outward winding

## Media specification

Media roll diameter(Max.)	Inside:127mm(5")max Outside:214mm(8.4")max
Media type	Continuous paper , label paper with gap, fan fold label paper, black mark paper Printing side outward rolling / inward rolling
Media rolling up method	Max.120 mm(4.72") Min.20 mm(0.78")
Media width (upper & bottom paper)	Max.0.254 mm(10 mil) Min.0.06 mm(2.36 mil)
The thickness of the paper (upper & bottom paper)	25.4 mm~38 mm(1"~1.5") 10~2286 mm(0.39"~90")
Media roll core size	Remark: If label length less than 25.4mm(1 inch), label paper with perforations are recommended, labels can be torn off easily.
Media length Label paper Gap	Min.2 mm(0.09")

### Features (GP-1125T)

Thermal transfer printing technology;  
Easy ribbon loading, easy print media loading;  
203 dpi high resolution printing;  
300 meters large ribbon capacity;  
8.4inch large print media can be held by Gprinter standard external holder;  
120mm(4.72inch) max. media width;  
Standard 4MB flash, 8MB DRAM memory;  
Standard 1" core label spindle.

